

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
25 September 2003 (25.09.2003)

PCT

(10) International Publication Number
WO 03/078038 A1(51) International Patent Classification⁷: **B01F 3/04**

(21) International Application Number: PCT/US03/07912

(22) International Filing Date: 13 March 2003 (13.03.2003)

(25) Filing Language: English

(26) Publication Language: English


(30) Priority Data:
10/098,798 14 March 2002 (14.03.2002) US(71) Applicant (for all designated States except US): **FLUOR CORPORATION** [US/US]; One Enterprise Drive, Aliso Viejo, CA 92656 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **JACOBS, Garry, E.** [US/US]; Fluor Corporation, One Fluor Daniel Drive, Aliso Viejo, CA 92656 (US). **STUPIN, Steven** [US/US];Fluor Corporation, One Fluor Daniel Drive, Aliso Viejo, CA 92656 (US). **MILLIKEN, Adam, S.** [US/US]; Fluor Corporation, One Fluor Daniel Drive, Aliso Viejo, CA 92656 (US).(74) Agent: **FISH, Robert, D.**; Rutan & Tucker, LLP, 611 Anton Blvd., Suite 1400, Costa Mesa, CA 92626 (US).(81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: METHODS AND APPARATUS FOR MIXING FLUIDS



(57) Abstract: A bubble cap (400) has a cap (430) with at least one slot (495) and a riser (420), configured with a skirt height (460) of at least 4 cm, such that $1.5 \times \text{Skirt Height (cm)} + [\text{Slot Length (cm)} - \text{Exposed Slot Height (cm)}]$ is greater than or equal to 7.5, and posed such that a liquid fluid and a gas flow co-currently upwardly in a space between the riser (420) and the cap (430).

WO 03/078038 A1